



STANDARD TYPE DRY COOLERS

| MODEL | CAPACITY 45/40°C - %35 Etilen glikol 30°C Air Inlet | AIR CAPACITY | FLOW CAPACITY | HEAT TRANSFER SURFACE | TUBE VOLUME | QUANTITY OF FAN | FAN MOTOR | | SOUND LEVEL | DIMENSIONS | | | | | | CONNECTIONS | | | | | |
|---------------------|--|--------------|---------------|--------------------------|-------------|-----------------|----------------|------|-------------|------------|------|------|------|-----|------|-------------|--|--|--|--|--|
| | | | | | | | POWER/CURRENT | | | A | B | D | H | G | E | | | | | | |
| | | | | | | | 3/400V , 50 Hz | | △ | | | | | | | | | | | | |
| | | | | | | | 880 d/d | | 880 d/d | | | | | | | | | | | | |
| kw | m³/h | m² | dm³ | adet | kw | A | dB(A) | mm | mm | mm | mm | mm | mm | Ø | | | | | | | |
| GKS Y/D 80.1.1-1625 | 49,5 | 18000 | 9,5 | 132,6 | 26,5 | 1x1 | 2,0 | 4,0 | 52 | 1280 | 1375 | 1230 | 1500 | 700 | 1320 | 1 1/2" | | | | | |
| GKS Y/D 80.1.1-1621 | 52,7 | 17350 | 10,1 | 156,5 | | | | | | | | | | | | | | | | | |
| GKS Y/D 80.2.1-1625 | 98,8 | 36000 | 18,9 | 265,2 | 53,0 | 1x2 | 4,0 | 8,0 | 55 | 2480 | 2590 | 1230 | 1500 | 700 | 1320 | 2" | | | | | |
| GKS Y/D 80.2.1-1621 | 105 | 34700 | 20,1 | 313 | | | | | | | | | | | | | | | | | |
| GKS Y/D 80.3.1-1625 | 156,4 | 54000 | 29,9 | 397,8 | 79,5 | 1x3 | 6,0 | 12,0 | 57 | 3680 | 3805 | 1230 | 1500 | 700 | 1320 | 2 1/2" | | | | | |
| GKS Y/D 80.3.1-1621 | 162,4 | 52050 | 31,0 | 469,6 | | | | | | | | | | | | | | | | | |
| GKS Y/D 80.4.1-1625 | 197,1 | 72000 | 37,7 | 530,4 | 106,1 | 1x4 | 8,0 | 16,0 | 58 | 4880 | 5020 | 1230 | 1500 | 700 | 1320 | 3" | | | | | |
| GKS Y/D 80.4.1-1621 | 209,4 | 69400 | 40,0 | 626,1 | | | | | | | | | | | | | | | | | |
| GKS Y/D 80.4.2-1625 | 197,5 | 72000 | 37,7 | 530,4 | 106,1 | 2x2 | 8,0 | 16,0 | 58 | 2480 | 2620 | 2350 | 1500 | 700 | 1320 | 3" | | | | | |
| GKS Y/D 80.4.2-1621 | 209,9 | 69400 | 40,0 | 626,1 | | | | | | | | | | | | | | | | | |
| GKS Y/D 80.6.2-1625 | 310 | 108000 | 59,3 | 795,6 | 159,1 | 2x3 | 12,0 | 24,0 | 60 | 3680 | 3820 | 2350 | 1500 | 700 | 1320 | 3" | | | | | |
| GKS Y/D 80.6.2-1621 | 324,8 | 104100 | 62,0 | 939,1 | | | | | | | | | | | | | | | | | |
| GKS Y/D 80.8.2-1625 | 394,1 | 144000 | 75,2 | 1061 | 212,1 | 2x4 | 16,0 | 32,0 | 61 | 4880 | 5050 | 2350 | 1500 | 700 | 1320 | 4" | | | | | |
| GKS Y/D 80.8.2-1621 | 418,8 | 138800 | 79,9 | 1252 | | | | | | | | | | | | | | | | | |